

## Rolamento cónico 303-22-XR-JTEKT - 303-22-XR-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/conico/303-22-xr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>			
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.				
22	56	17.25	16	13	36.3	36.6	7 700	10 000	303/22XR					
Dimension series to ISO 955 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>a</sub> min.	d <sub>a</sub> max.	D <sub>s</sub> min.	D <sub>s</sub> max.	S <sub>s</sub> min.	S <sub>s</sub> max.	r <sub>a</sub> min.	r <sub>a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
—	15.7	30.5	31	47.5	44	52	3	4	1.5	1.5	0.59	1.02	0.56	0.210

### CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
Nº Ean13	3663952400440
Diâmetro interior	22 mm
Diâmetro exterior	56 mm
Espessura	17.25 mm
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE