

## Rolamento cónico 30315-DJR-JTEKT - 30315-DJR-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/conico/30315-djr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



| Boundary dimensions (mm)               |                    |                          |                      | Basic load ratings (kN) |                      |                      |                      | Limiting speeds (min <sup>-1</sup> ) |                      | Bearing No. <sup>1)</sup> |                                   |                                   |                      |      |
|--|--------------------|--------------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|----------------------|---------------------------|-----------------------------------|-----------------------------------|----------------------|------|
| d                                      | D                  | T                        | B                    | C                       | C <sub>r</sub>       | C <sub>0r</sub>      | Grease lub.          | Oil lub.                             |                      |                           |                                   |                                   |                      |      |
| 75                                     | 160                | 40                       | 37                   | 28                      | 213                  | 254                  | 2 100                | 2 900                                | 30315DJR             |                           |                                   |                                   |                      |      |
| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) |                      |                         |                      |                      |                      |                                      |                      |                           |                                   |                                   |                      |      |
|  |                    | d <sub>1a</sub> min.     | d <sub>1a</sub> max. | D <sub>1a</sub> min.    | D <sub>1a</sub> max. | S <sub>1a</sub> min. | S <sub>1a</sub> max. | r <sub>1a</sub> min.                 | r <sub>1a</sub> max. | Constant e                | Axial load factors Y <sub>1</sub> | Axial load factors Y <sub>0</sub> | (Refer. 1) Mass (kg) |      |
| 7GB                                    | 49.9               | 89                       | 91                   | 148                     | 127                  | 151                  | 6                    | 14                                   | 2.5                  | 2                         | 0.83                              | 0.73                              | 0.40                 | 3.45 |

### CARACTERÍSTICAS DO PRODUTO

|                   |               |
|-------------------|---------------|
| Marca             | JTEKT         |
| Nº Ean13          | 3663952409290 |
| Diâmetro interior | 75 mm         |
| Diâmetro exterior | 160 mm        |
| Espessura         | 40 mm         |
| Embalagem         | 1             |

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE