


## Rolamento cónico 32318-JR-JTEKT - 32318-JR-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/conico/32318-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



| Boundary dimensions (mm)               |                    |                          |                      |                      | Basic load ratings (kN) |                      |                      |                      | Limiting speeds (min <sup>-1</sup> ) |            | Bearing No. <sup>1)</sup> |                |                      |      |
|--|--------------------|--------------------------|----------------------|----------------------|-------------------------|----------------------|----------------------|----------------------|--------------------------------------|------------|---------------------------|----------------|----------------------|------|
| d                                      | D                  | T                        | B                    | C                    | C <sub>r</sub>          | C <sub>0r</sub>      | C <sub>90</sub>      | C <sub>100</sub>     | Grease lub.                          | Oil lub.   |                           |                |                      |      |
| 90                                     | 190                | 67.5                     | 64                   | 53                   | 461                     | 614                  |                      |                      | 2 100                                | 2 800      | 32318JR                   |                |                      |      |
| Dimension series to ISO 955 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) |                      |                      |                         |                      |                      |                      |                                      | Constant e | Axial load factors        |                | (Refer. 1) Mass (kg) |      |
|  |                    | d <sub>1a</sub> min.     | d <sub>1a</sub> max. | d <sub>2a</sub> min. | d <sub>2a</sub> max.    | S <sub>1a</sub> min. | S <sub>1a</sub> max. | r <sub>1a</sub> min. | r <sub>1a</sub> max.                 |            | Y <sub>1</sub>            | Y <sub>0</sub> |                      |      |
| 260                                    | 46.6               | 108                      | 108                  | 176                  | 157                     | 177                  | 5                    | 14.5                 | 3                                    | 2.5        | 0.35                      | 1.74           | 0.96                 | 8.61 |

### CARACTERÍSTICAS DO PRODUTO

|                   |               |
|-------------------|---------------|
| Marca             | JTEKT         |
| Nº Ean13          | 4549250125249 |
| Diâmetro interior | 90 mm         |
| Diâmetro exterior | 190 mm        |
| Espessura         | 67.5 mm       |
| Peso              | 8061 g        |
| Embalagem         | -             |

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE