


Rolamento cónico 32320-JR-JTEKT - 32320-JR-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/conico/32320-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | | | |
|----------------------------------------|--------------------|--------------------------|---------------------|-------------------------|---------------------|---------------------|---------------------|--------------------------------------|---------------------|---------------------------|--------------------|----------------|----------------------|------|
| d | D | T | B | C | C _r | C _{0r} | Grease lub. | Oil lub. | | | | | | |
| 100 | 215 | 77.5 | 73 | 60 | 579 | 783 | 1 800 | 2 400 | 32320JR | | | | | |
| Dimension series to ISO 955 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) | |
| | | d ₁ min. | d ₂ max. | D ₁ max. | D ₂ min. | S ₁ min. | S ₂ min. | r ₁ min. | r ₂ max. | | Y ₁ | Y ₀ | | |
| 260 | 53.9 | 118 | 123 | 201 | 177 | 200 | 8 | 17.5 | 3 | 2.5 | 0.35 | 1.74 | 0.96 | 13.0 |

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| Nº Ean13 | 3663952410623 |
| Diâmetro interior | 100 mm |
| Diâmetro exterior | 215 mm |
| Espessura | 77.5 mm |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE