

Rolamento cónico 30322-JTEKT - 30322-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/conico/30322-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ |
|--------------------------|-----|------|----|----|-------------------------|-----------------|-----------------|------------------|--------------------------------------|----------|---------------------------|
| d | D | T | B | C | C _r | C _{0r} | C ₉₀ | C ₁₀₀ | Grease lub. | Oil lub. | |
| 110 | 240 | 54.5 | 50 | 42 | 407 | 475 | 1 600 | 2 100 | | | 30322 |

| Dimension series to ISO 955 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | | | Constant e | Axial load factors | | (Refer. 1) Mass (kg) |
|--|--------------------|--------------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------|----------------|------------|--------------------|------|----------------------|
| | | d _{1a} min. | d _{1a} max. | D _{1a} min. | D _{1a} max. | S _{1a} min. | S _{1a} max. | r _{1a} min. | r _{1a} max. | Y ₁ | Y ₀ | | | | |
| — | 44.8 | 128 | 141 | 226 | 206 | 222 | 8 | 12.5 | 3 | 2.5 | 0.35 | 1.73 | 0.95 | 10.4 | |

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| Nº Ean13 | 4549250122453 |
| Diâmetro interior | 110 mm |
| Diâmetro exterior | 240 mm |
| Espessura | 54.5 mm |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE