


## Rolamento cónico 32248-JTEKT - 32248-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/conico/32248-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.	
240	440	127	120	100	5	4	1 530	2 480	740	980	32248

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)										Constant e	Axial load factors		(Refer. 1) Mass (kg)
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	d <sub>2a</sub> min.	d <sub>2a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>	
—	106.1	262	282	422	365	415	16	14	4	3	0.43	1.39	0.77	76.4	

## CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
Nº Ean13	3663952421735
Diâmetro interior	240 mm
Diâmetro exterior	440 mm
Espessura	127 mm
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE