


## Rolamento cónico 16137-16284-JTEKT - 16137-16284-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/conico/16137-16284-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



| Boundary dimensions (mm) |          |          |          |          |                              |                              | Basic load ratings (kN) |                       | Limiting speeds (min <sup>-1</sup> ) |          |
|--------------------------|----------|----------|----------|----------|------------------------------|------------------------------|-------------------------|-----------------------|--------------------------------------|----------|
| <i>d</i>                 | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r<sub>a</sub></i><br>max. | <i>r<sub>b</sub></i><br>max. | <i>C<sub>r</sub></i>    | <i>C<sub>10</sub></i> | Grease lub.                          | Oil lub. |
| 34.925                   | 72.238   | 20.638   | 20.638   | 19.875   | 3.6                          | 1.2                          | 49.7                    | 61.3                  | 5 600                                | 7 400    |

| Bearing No. |            | Load center (mm) | Mounting dimensions (mm) |                      |                      |                      |                              |                              | Constant | Axial load factors   |                      | (Refer.) Mass (kg) |            |
|-------------|------------|------------------|--------------------------|----------------------|----------------------|----------------------|------------------------------|------------------------------|----------|----------------------|----------------------|--------------------|------------|
| Inner ring  | Outer ring | <i>a</i>         | <i>d<sub>a</sub></i>     | <i>d<sub>b</sub></i> | <i>D<sub>a</sub></i> | <i>D<sub>b</sub></i> | <i>r<sub>a</sub></i><br>max. | <i>r<sub>b</sub></i><br>max. | <i>e</i> | <i>Y<sub>1</sub></i> | <i>Y<sub>2</sub></i> | Inner ring         | Outer ring |
| 16137       | 16284      | 16.6             | 46.5                     | 40.5                 | 63.0                 | 67.0                 | 3.6                          | 1.2                          | 0.40     | 1.49                 | 0.82                 | 0.236              | 0.144      |

### CARACTERÍSTICAS DO PRODUTO

|                   |               |
|-------------------|---------------|
| Marca             | JTEKT         |
| Nº Ean13          | 3663952426310 |
| Diâmetro interior | 34.925 mm     |
| Diâmetro exterior | 72.238 mm     |
| Espessura         | 20.638 mm     |
| Embalagem         | 1             |

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE