


## Rolamento cónico 26877R-26822-JTEKT - 26877R-26822-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/conico/26877r-26822-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> <sub>a</sub> max.	<i>r</i> <sub>b</sub> max.	<i>C</i> <sub>r</sub>	<i>C</i> <sub>10</sub>	Grease lub.	Oil lub.
36.512	79.375	23.812	25.400	19.050	0.8	0.8	81.1	105	5 000	6 700

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring		<i>d</i> <sub>a</sub>	<i>d</i> <sub>b</sub>	<i>D</i> <sub>a</sub>	<i>D</i> <sub>b</sub>	<i>r</i> <sub>a</sub> max.	<i>r</i> <sub>b</sub> max.		<i>Y</i> <sub>1</sub>	<i>Y</i> <sub>2</sub>	Inner ring	Outer ring
26877R	26822	16.4	44.0	43.0	71.0	74.0	0.8	0.8	0.32	1.88	1.04	0.404	0.186

### CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
Nº Ean13	3663952426471
Diâmetro interior	36.512 mm
Diâmetro interior	1 7/16" inch
Diâmetro exterior	79.375 mm
Diâmetro exterior	3 1/8" inch
Espessura	23.812 mm
Espessura	15/16" inch
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE