


Rolamento cónico 2788R-2735X-JTEKT - 2788R-2735X-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/conico/2788r-2735x-jtekt>

Single-row tapered roller bearings
inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _a max.	<i>r</i> _b max.	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
38.100	73.025	23.812	25.664	19.050	3.6	0.8	74.1	92.2	5 400	7 200

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring		<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.		<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
2788R	2735X	15.9	50.0	43.5	66.0	69.0	3.6	0.8	0.30	1.98	1.09	0.308	0.134

CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
Nº Ean13	3663952426600
Diâmetro interior	38.1 mm
Diâmetro exterior	73.025 mm
Espessura	23.812 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE