


Rolamento cónico 27880-27820-JTEKT - 27880-27820-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/conico/27880-27820-jtekt>

Single-row tapered roller bearings
inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _a max.	<i>r</i> _b max.	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
38.100	80.035	24.608	23.698	18.912	0.8	1.6	73.2	91.6	5 200	6 900

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring		<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.		<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
27880	27820	22.2	48.0	47.0	68.0	75.0	0.8	1.6	0.56	1.07	0.59	0.378	0.208

CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
Nº Ean13	3663952426631
Diâmetro interior	38.1 mm
Diâmetro exterior	80.035 mm
Espessura	24.608 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE