

Rolamento cónico 368S-362A-JTEKT - 368S-362A-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/conico/368s-362a-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r_a</i> max.	<i>r_b</i> max.	<i>C_r</i>	<i>C₁₀</i>	Grease lub.	Oil lub.
51.592	88.900	20.638	22.225	16.513	2.0	1.2	74.3	87.3	4 400	5 800

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d_a</i>	<i>d_b</i>	<i>D_a</i>	<i>D_b</i>	<i>r_a</i> max.	<i>r_b</i> max.	<i>e</i>	<i>Y₁</i>	<i>Y₂</i>	Inner ring	Outer ring
368S	362A	16.1	59.0	56.0	81.0	84.0	2.0	1.2	0.32	1.88	1.03	0.321	0.164

CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
N° Ean13	3663952427829
Diâmetro interior	51.592 mm
Diâmetro interior	2 1/32" inch
Diâmetro exterior	88.9 mm
Diâmetro exterior	3 1/2" inch
Espessura	20.638 mm
Espessura	13/16" inch
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE