


## Rolamento cónico 756A-752-JTEKT - 756A-752-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rosos/conico/756a-752-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r<sub>a</sub></i> max.	<i>r<sub>b</sub></i> max.	<i>C<sub>r</sub></i>	<i>C<sub>10</sub></i>	Grease lub.	Oil lub.
79.375	161.925	47.625	48.260	38.100	7.9	3.2	273	391	2 400	3 200

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer.) Mass (kg) Inner ring Outer ring	
Inner ring	Outer ring		<i>d<sub>a</sub></i>	<i>d<sub>b</sub></i>	<i>D<sub>a</sub></i>	<i>D<sub>b</sub></i>	<i>r<sub>a</sub></i> max.	<i>r<sub>b</sub></i> max.		<i>Y<sub>1</sub></i>	<i>Y<sub>2</sub></i>		
756A	752	35.5	106.0	91.0	144.0	150.0	7.9	3.2	0.34	1.76	0.97	2.95	1.59

### CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
Nº Ean13	3663952429267
Diâmetro interior	79.375 mm
Diâmetro interior	3 1/8" inch
Diâmetro exterior	161.925 mm
Diâmetro exterior	6 3/8" inch
Espessura	47.625 mm
Espessura	1 7/8" inch
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE