

Rolamento cónico 6581XR-6535-JTEKT - 6581XR-6535-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/conico/6581xr-6535-jtekt>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|----------|----------|----------|----------|-------------------------------|-------------------------------|-------------------------|------------------------|--------------------------------------|----------|
| <i>d</i> | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r</i> _a max. | <i>r</i> _b max. | <i>C</i> _r | <i>C</i> ₁₀ | Grease lub. | Oil lub. |
| 90.000 | 161.925 | 53.975 | 55.100 | 42.862 | 3.0 | 3.2 | 316 | 471 | 2 400 | 3 200 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Constant | Axial load factors | | (Refer.) Mass (kg) | |
|-------------|------------|------------------|--------------------------|-----------------------|-----------------------|-----------------------|-------------------------------|-------------------------------|----------|-----------------------|-----------------------|--------------------|------------|
| Inner ring | Outer ring | <i>a</i> | <i>d</i> _a | <i>d</i> _b | <i>D</i> _a | <i>D</i> _b | <i>r</i> _a max. | <i>r</i> _b max. | <i>e</i> | <i>Y</i> ₁ | <i>Y</i> ₂ | Inner ring | Outer ring |
| 6581XR | 6535 | 41.0 | 102.0 | 98.0 | 141.0 | 154.0 | 3.0 | 3.2 | 0.40 | 1.50 | 0.82 | 3.02 | 1.65 |

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| Nº Ean13 | 3663952429731 |
| Diâmetro interior | 90 mm |
| Diâmetro exterior | 161.925 mm |
| Espessura | 53.975 mm |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE