


Rolamento cónico

LM245848-LM245810-JTEKT - LM245848-LM245810-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/conico/lm245848-lm245810-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _a max.	<i>r</i> _b max.	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
231.775	317.500	47.625	52.388	30.513	3.2	3.2	488	928	970	1 300

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring		<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.		<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
LM245848	LM245810	50.5	244.0	240.0	309.0	312.0	3.2	3.2	0.33	1.80	0.99	8.02	2.78

CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
Nº Ean13	3663952431826
Diâmetro interior	231.775 mm
Diâmetro interior	9 1/8" inch
Diâmetro exterior	317.5 mm
Diâmetro exterior	12 1/2" inch
Espessura	47.625 mm
Espessura	1 7/8" inch
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE