

Rolamento de agulhas MHKM1010-JTEKT - MHKM1010-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/mhkm1010-jtekt>

Drawn cup needle roller bearings Koyo

| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ | |
|--------------------------|-----|-----|-------------|-------------------------|----------|--------------------------------------|------------------------------|-----------------|
| F_w | D | C | b min. | C_0 | C_{0r} | Oil lub. | Caged type With open ends | With closed end |
| 10 | 17 | 10 | 8.4 | 4.85 | 4.25 | 30 000 | | MHKM1010 |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|--------------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (H6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| — | — | 9.991 | 10.000 | 16.977 | 16.995 | 7.8 | 8.9 |

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| Nº Ean13 | 3663952469584 |
| Diâmetro interior | 10 mm |
| Diâmetro exterior | 17 mm |
| Espessura | 10 mm |
| Peso | 8.9 g |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE