


## Rolamento de agulhas BHTM1510-JTEKT - BHTM1510-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/bhtm1510-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	Bearing No. <sup>2)</sup>
$F_w$	$D$	$C$	$b$ min.	$C_0$	$C_{0r}$	Oil lub.	Caged type With open ends With closed end
15	22	10	8.4	6.35	6.45	23 000	<b>BHTM1510</b>

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (d6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	14.989	15.000	21.972	21.993	9.9	11

### CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
Nº Ean13	3663952470184
Diâmetro interior	15 mm
Diâmetro exterior	22 mm
Espessura	10 mm
Peso	9.9 g
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE