

Rolamento de agulhas 16BTM2212A-JTEKT - 16BTM2212A-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/16btm2212a-jtekt>

Drawn cup needle roller bearings 



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ²⁾ | |
|--------------------------|-----|-----|----------|-------------------------|----------|--------------------------------------|------------|---------------------------|-----------------|
| F_w | D | C | b min. | C_0 | C_{0e} | Oil lub. | Caged type | | |
| | | | | | | | | With open ends | With closed end |
| 16 | 22 | 12 | 9.3 | 7.80 | 9.80 | 22 000 | 16BTM2212A | | |

| Full complement type | | Recommended dimensions (mm) | | | | Refer. Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|-----------------------------|----------------------|-----------------|-----------------|
| With open ends | With closed end | Shaft dia. (H6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| — | — | 15.989 | 16.000 | 21.991 ⁴⁾ | 22.012 ⁴⁾ | 11 | 12 |

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| N° Ean13 | 3663952470283 |
| Diâmetro interior | 16 mm |
| Diâmetro interior | 0.63" inch |
| Diâmetro exterior | 22 mm |
| Diâmetro exterior | 0.866" inch |
| Espessura | 12 mm |
| Espessura | 0.472" inch |
| Peso | 11 g |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE