


Rolamento de agulhas BHTM1616A-JTEKT - BHTM1616A-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/bhtm1616a-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾
F_w	D	C	b min.	C_0	C_{0r}	Oil lub.	Caged type With open ends With closed end
16	24	16	13.3	12.2	14.9	21 000	BHTM1616A

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (f6) min.	max.	Housing bore dia. (H7) min.	max.	With open ends	With closed end
—	—	15.989	16.000	23.991 ⁽⁴⁾	24.012 ⁽⁴⁾	20	23

CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
Nº Ean13	3663952470368
Diâmetro interior	16 mm
Diâmetro exterior	24 mm
Espessura	16 mm
Peso	20 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE