

Rolamento de agulhas BTM202730-JTEKT - BTM202730-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/btm202730-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ |
|--------------------------|-----|-----|-------------|-------------------------|----------|--------------------------------------|--|
| F_w | D | C | b min. | C_0 | C_{0r} | Oil lub. | Caged type With open ends With closed end |
| 4 | 27 | 30 | 27.3 | 25.4 | 43.8 | 18 000 | BTM202730 |

| Full complement type | | Recommended dimensions (mm) | | | | Refer. Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|--------------------------------|--------|-----------------|-----------------|
| With open ends | With closed end | Shaft dia. (f6) min. | max. | Housing bore dia. (H7) min. | max. | With open ends | With closed end |
| — | — | 19.987 | 20.000 | 26.972 | 26.993 | 40 | 45 |

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| Nº Ean13 | 3663952471006 |
| Diâmetro interior | 20 mm |
| Diâmetro exterior | 27 mm |
| Espessura | 30 mm |
| Peso | 40 g |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE