

Rolamento de agulhas 22BM2812-JTEKT - 22BM2812-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/22bm2812-jtekt>

Drawn cup needle roller bearings Koyo

Full complement type
With open ends

BM, BH-M

| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ |
|--------------------------|-----|-----|-------------|-------------------------|----------|--------------------------------------|---|
| F_w | D | C | b min. | C_r | C_{0r} | Oil lub. | Caged type With open ends With closed end |
| 22 | 28 | 12 | 9.6 | 11.8 | 22.9 | 5 800 | |

| Full complement type With open ends With closed end | Recommended dimensions (mm) | | | | Refer. Mass (g) | |
|---|-----------------------------|--------|--------------------------------|--------|-----------------|-----------------|
| | Shaft dia. (F6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| 22BM2812 | 21.987 | 22.000 | 27.972 | 27.993 | 16 | 18 |

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| Nº Ean13 | 3663952471051 |
| Diâmetro interior | 22 mm |
| Diâmetro exterior | 28 mm |
| Espessura | 12 mm |
| Peso | 16 g |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE