


Rolamento de agulhas MKM2516-JTEKT - MKM2516-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/mkm2516-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ |
|--------------------------|-----|-----|-------------|-------------------------|----------|--------------------------------------|---|
| F_w | D | C | b min. | C_r | C_{0r} | Oil lub. | Caged type With open ends With closed end |
| 25 | 32 | 16 | 13.3 | 15.3 | 24.6 | 14 000 | MKM2516 |

| Full complement type | | Recommended dimensions (mm) | | | | (Refer.) Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|--------------------------------|--------|-------------------|-----------------|
| With open ends | With closed end | Shaft dia. (φ6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| — | — | 24.987 | 25.000 | 31.967 | 31.992 | 26 | 30 |

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| Nº Ean13 | 3663952471365 |
| Diâmetro interior | 25 mm |
| Diâmetro interior | 0.984" inch |
| Diâmetro exterior | 32 mm |
| Diâmetro exterior | 1.26" inch |
| Espessura | 16 mm |
| Espessura | 0.63" inch |
| Peso | 30 g |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE