


Rolamento de agulhas BHTM2510A-JTEKT - BHTM2510A-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/bhtm2510a-jtekt>

Drawn cup needle roller bearings Koyo



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds (min ⁻¹)	Bearing No. ²⁾
F_w	D	C	b min.	C_r	C_{0r}	Oil lub.	Caged type With open ends With closed end
25	33	10	—	8.90	10.3	14 000	BHTM2510A

Full complement type		Recommended dimensions (mm)				(Refer.) Mass (g)	
With open ends	With closed end	Shaft dia. (φ6) min.	max.	Housing bore dia. (N7) min.	max.	With open ends	With closed end
—	—	24.987	25.000	32.989 ⁽⁴⁾	33.014 ⁽⁴⁾	18	—

CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
N° Ean13	3663952471433
Diâmetro interior	25 mm
Diâmetro interior	0.984" inch
Diâmetro exterior	33 mm
Diâmetro exterior	1.299" inch
Espessura	10 mm
Espessura	0.394" inch
Peso	18 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE