

## Rolamento de agulhas 28BTM3516-JTEKT - 28BTM3516-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/28btm3516-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) |     |     |             | Basic load ratings (kN) |          | Limiting speeds (min <sup>-1</sup> ) | Bearing No. <sup>2)</sup>                    |
|--------------------------|-----|-----|-------------|-------------------------|----------|--------------------------------------|--|
| $F_w$                    | $D$ | $C$ | $b$<br>min. | $C_0$                   | $C_{0r}$ | Oil lub.                             | Caged type<br>With open ends With closed end |
| 28                       | 35  | 16  | 13.3        | 15.9                    | 26.2     | 13 000                               | <b>28BTM3516</b>                             |

| Full complement type |                 | Recommended dimensions (mm) |        |                                |        | (Refer.) Mass (g) |                 |
|----------------------|-----------------|-----------------------------|--------|--------------------------------|--------|-------------------|-----------------|
| With open ends       | With closed end | Shaft dia. (φ6)<br>min.     | max.   | Housing bore dia. (N7)<br>min. | max.   | With open ends    | With closed end |
| —                    | —               | 27.987                      | 28.000 | 34.967                         | 34.992 | 28                | 31              |

### CARACTERÍSTICAS DO PRODUTO

|                   |               |
|-------------------|---------------|
| Marca             | JTEKT         |
| Nº Ean13          | 4549250107122 |
| Diâmetro interior | 28 mm         |
| Diâmetro exterior | 35 mm         |
| Espessura         | 16 mm         |
| Peso              | 28 g          |
| Embalagem         | 1             |

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE