


Rolamento de agulhas BTM384512A-JTEKT - BTM384512A-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/btm384512a-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | Bearing No. ²⁾ |
|--------------------------|----|----|--------|-------------------------|-----------------|--------------------------------------|--|
| F _w | D | C | b min. | C ₁₀ | C ₉₀ | Oil lub. | Caged type With open ends With closed end |
| 38 | 45 | 12 | — | 12.7 | 23.0 | 9 800 | BTM384512A |

| Full complement type | | Recommended dimensions (mm) | | | | Refer. Mass (g) | |
|----------------------|-----------------|-----------------------------|--------|-----------------------------|--------|-----------------|-----------------|
| With open ends | With closed end | Shaft dia. (d6) min. | max. | Housing bore dia. (N7) min. | max. | With open ends | With closed end |
| — | — | 37.984 | 38.000 | 44.967 | 44.992 | 29 | — |

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| Nº Ean13 | 3663952472447 |
| Diâmetro interior | 38 mm |
| Diâmetro interior | 1.496" inch |
| Diâmetro exterior | 45 mm |
| Diâmetro exterior | 1.772" inch |
| Espessura | 12 mm |
| Espessura | 0.472" inch |
| Peso | 29 g |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE