

## Rolamento de agulhas 50BTM5825-JTEKT - 50BTM5825-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/50btm5825-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) |    |    |        | Basic load ratings (kN) |                 | Limiting speeds (min <sup>-1</sup> ) | Bearing No. <sup>2)</sup>                       |
|--------------------------|----|----|--------|-------------------------|-----------------|--------------------------------------|---|
| F <sub>w</sub>           | D  | C  | b min. | C <sub>0</sub>          | C <sub>0r</sub> | Oil lub.                             | Caged type<br>With open ends    With closed end |
| 50                       | 58 | 25 | 22.3   | 35.9                    | 82.5            | 7 500                                | <b>50BTM5825</b>                                |

| Full complement type |                 | Recommended dimensions (mm) |        |                             |        | Refer. Mass (g) |                 |
|----------------------|-----------------|-----------------------------|--------|-----------------------------|--------|-----------------|-----------------|
| With open ends       | With closed end | Shaft dia. (f6) min.        | max.   | Housing bore dia. (N7) min. | max.   | With open ends  | With closed end |
| —                    | —               | 49.984                      | 50.000 | 57.961                      | 57.991 | 86              | 97              |

### CARACTERÍSTICAS DO PRODUTO

|                   |               |
|-------------------|---------------|
| Marca             | JTEKT         |
| Nº Ean13          | 3663952472911 |
| Diâmetro interior | 50 mm         |
| Diâmetro exterior | 58 mm         |
| Espessura         | 25 mm         |
| Peso              | 86 g          |
| Embalagem         | 1             |

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE