


## Rolamento de agulhas 55BTM6720A-JTEKT - 55BTM6720A-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/55btm6720a-jtekt>

Drawn cup needle roller bearings Koyo



| Boundary dimensions (mm) |     |     |           | Basic load ratings (kN) |          | Limiting speeds (min <sup>-1</sup> ) | Bearing No. <sup>2)</sup>                    |
|--------------------------|-----|-----|-----------|-------------------------|----------|--------------------------------------|--|
| $F_w$                    | $D$ | $C$ | $b$<br>mm | $C_0$                   | $C_{0r}$ | Oil lub.                             | Caged type<br>With open ends With closed end |
| 55                       | 67  | 20  | —         | 36.4                    | 63.1     | 6 700                                | 55BTM6720A                                   |

| Full complement type |                 | Recommended dimensions (mm) |                              |        |        | (Refer.) Mass (g) |                 |
|----------------------|-----------------|-----------------------------|------------------------------|--------|--------|-------------------|-----------------|
| With open ends       | With closed end | Shaft dia. (H6)<br>mm       | Housing bore dia. (H7)<br>mm | min.   | max.   | With open ends    | With closed end |
| —                    | —               | 54.981                      | 55.000                       | 66.961 | 62.991 | 110               | —               |

### CARACTERÍSTICAS DO PRODUTO

|                   |               |
|-------------------|---------------|
| Marca             | JTEKT         |
| Nº Ean13          | 4549250138065 |
| Diâmetro interior | 55 mm         |
| Diâmetro exterior | 67 mm         |
| Espessura         | 20 mm         |
| Peso              | 110 g         |
| Embalagem         | 1             |
| Padrão            | Nenhuma norma |

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE