


## Rolamento de rolos NN3030K-JTEKT - NN3030K-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/rolos/nn3030k-jtekt>

Double-row cylindrical roller bearings ——— Koyo



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )		Bearing No.	
d	D	B	r min.	F <sub>w</sub>	C	C <sub>107</sub>	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
150	225	56	2.1	208	334	587	2 500	3 000	NN3030K	NN3030K

Mounting dimensions (mm)		Cylindrical bore		Tapered bore		Mass (kg)	
d <sub>a</sub> min.	d <sub>a</sub> max.	D <sub>a</sub> min.	D <sub>a</sub> max.	r <sub>a</sub> min.	r <sub>a</sub> max.	Cylindrical bore	Tapered bore
161	—	—	214	208	2	7.74	7.50

### CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
Nº Ean13	3663952473222
Diâmetro interior	150 mm
Diâmetro exterior	225 mm
Espessura	56 mm
Peso	7500 g
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE