

Rolamento de rolos NN3040K-JTEKT - NN3040K-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/rolos/nn3040k-jtekt>

Double-row cylindrical roller bearings 



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min ⁻¹)		Bearing No.		
d	D	B	r _{min}	F _{0.2}	E _{0.2}	C ₁₀	C ₀₂	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
200	310	82	2.1	—	252	638	1 120	1 700	2 100	—	NN3040K

		Mounting dimensions (mm)						(Refer.) Mass (kg)	
Cylindrical bore	Tapered bore	d _a		D _a		r _s		Cylindrical bore	Tapered bore
		min.	max.	min.	max.	min.	max.		
		211	—	—	299	285	2	22.5	21.8

CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
Nº Ean13	3663952473420
Diâmetro interior	200 mm
Diâmetro interior	7.874" inch
Diâmetro exterior	310 mm
Diâmetro exterior	12.205" inch
Espessura	82 mm
Espessura	3.228" inch
Peso	21800 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE