


Rolamento de rolos NNU4944K-JTEKT - NNU4944K-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/rolos/nnu4944k-jtekt>

Double-row cylindrical roller bearings — Koyo



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min ⁻¹)		Bearing No.	
d	D	B	r min.	F _w	E _a	C	C ₁₀₇	Grease lub.	Oil lub.	NN Cylindrical bore Tapered bore
220	300	80	2.1	244	—	501	1 220	1 700	2 000	

Mounting dimensions (mm)		d _a		D _a	r _a		(Refer.) Mass (kg)		
NNU Cylindrical bore	NNU Tapered bore	min.	max.	min.	max.	min.	max.	Cylindrical bore	Tapered bore
	NNU4944K	231	241	248	289	—	2	16.7	16.0

CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
Nº Ean13	3663952473444
Diâmetro interior	220 mm
Diâmetro exterior	300 mm
Espessura	80 mm
Peso	16000 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE