

Rolamento de rolos NN3016K-JTEKT - NN3016K-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/rolos/nn3016k-jtekt>

Double-row cylindrical roller bearings ————— **Koyo**



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min ⁻¹)		Bearing No.		
<i>d</i>	<i>D</i>	<i>B</i>	<i>r</i> _{min}	<i>F</i> _w	<i>E</i> _a	<i>C</i> ₁₀	<i>C</i> ₀₂	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
80	125	34	1.1	—	113	119	166	4 800	5 800	—	—

		Mounting dimensions (mm)						(Refer.) Mass (kg)	
Cylindrical bore	Tapered bore	<i>d</i> _a		<i>D</i> _a		<i>r</i> _s		Cylindrical bore	Tapered bore
		min.	max.	min.	max.	min.	max.		
—	—	86.5	—	—	118.5	114	1	1.55	1.50

CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
Nº Ean13	3663952473758
Diâmetro interior	80 mm
Diâmetro exterior	125 mm
Espessura	34 mm
Peso	1500 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE