

## Rolamento de rolos NN3092K-JTEKT - NN3092K-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/rolos/nn3092k-jtekt>

Double-row cylindrical roller bearings ————— **Koyo**



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds (min <sup>-1</sup> )		Bearing No.		
d	D	B	r <sub>min</sub>	F <sub>w</sub>	E <sub>0</sub>	C	C <sub>107</sub>	Grease lub.	Oil lub.	Cylindrical bore	Tapered bore
460	680	163	6	—	827	2700	5480	570	690	—	—
				Mounting dimensions (mm)				(Refer.) Mass (kg)			
Cylindrical bore		Tapered bore		d <sub>a</sub> min.	d <sub>a</sub> max.	d <sub>s</sub> min.	d <sub>s</sub> max.	D <sub>s</sub> min.	r <sub>s</sub> max.	Cylindrical bore	Tapered bore
				484	—	—	656	632	5	201	195

## CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
Nº Ean13	3663952474212
Diâmetro interior	460 mm
Diâmetro exterior	680 mm
Espessura	163 mm
Peso	195000 g
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE