

Rolamento de rolos NQ29-30-JTEKT - NQ29-30-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/rolos/nq29-30-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds ¹⁾ (min ⁻¹)		Bearing No. Without inner ring
F_w	d	D	B	C_r	C_{10}	Oil lub.			
29	25	38	30	0.3	28.9	54.3	16 000	NQ29/30	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring				
	d_a	D_a	r_a	0.085	0.125				
	min.	max.	max.						
	27	36	0.3						

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
Nº Ean13	3663952482620
Diâmetro interior	29 mm
Diâmetro exterior	38 mm
Espessura	30 mm
Peso	85 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE