


Rolamento de rolos NQI25-30-JTEKT - NQI25-30-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/rolos/nqi25-30-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 ~ 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No. Without inner ring
F_w	d	D	B	B_1	C_r	C_{10}	Oil lub.		
29	25	38	30	—	0.3	28.9	54.3	16 000	—
Mounting dimensions (mm)					(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring					Without inner ring	With inner ring			
					d_1	D_1	r_1		
					min.	max.	max.		
					27	36	0.3	0.085	0.125

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
Nº Ean13	3663952482637
Diâmetro interior	25 mm
Diâmetro exterior	38 mm
Espessura	30 mm
Peso	125 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE