

## Rolamento de rolos 25NQI4425A-JTEKT - 25NQI4425A-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/rolos/25nqi4425a-jtekt>

Machined ring needle roller bearings Koyo

$F_w$  29 ~ 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No. Without inner ring	
$F_w$	d	D	B	$C_r$	$C_{0r}$	Oil lub.			
30	25	44	25	36.0	48.8	14 000	—	—	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				$d_a$	$D_a$	$r_a$	Without inner ring	With inner ring	
25NQI4425A				27	42	0.3	—	0.161	—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
Nº Ean13	3663952482767
Diâmetro interior	25 mm
Diâmetro exterior	44 mm
Espessura	25 mm
Peso	161 g
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE