


Rolamento de rolos NQI28-20-JTEKT - NQI28-20-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/rolos/nqi28-20-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 ~ 37 mm

With inner ring



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. Without inner ring | |
|--------------------------|-----|-----|-----|-------|-------------------------|-----------------|----------------------------------------------------|--------|-----------------------------------|---|
| F_w | d | D | B | B_1 | C_r | C_{10} | Oil lub. | | | |
| 32 | 28 | 42 | 20 | — | 0.3 | 24.3 | 39.4 | 14 000 | — | |
| Mounting dimensions (mm) | | | | | (Refer.) Mass (kg) | | (Refer.) Applicable inner ring No. | | | |
| With inner ring | | | | | Without inner ring | With inner ring | | | | |
| NQI28/20 | | | | | 30 | 40 | 0.3 | 0.070 | 0.098 | — |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| Nº Ean13 | 3663952482781 |
| Diâmetro interior | 28 mm |
| Diâmetro exterior | 42 mm |
| Espessura | 20 mm |
| Peso | 98 g |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE