


## Rolamento de rolos NQI28-30-JTEKT - NQI28-30-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/rolos/nqi28-30-jtekt>

### Machined ring needle roller bearings Koyo

$F_w$  29 ~ 37 mm

With inner ring



Boundary dimensions (mm)				Basic load ratings (kN)			Limiting speeds <sup>1)</sup> (min <sup>-1</sup> )		Bearing No. Without inner ring
$F_w$	d	D	B	$C_r$	$C_{10}$	Oil lub.			
32	28	42	30	34.4	61.6	14 000		—	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring				Without inner ring	With inner ring				
NQI28/30				30	40	0.3	0.104	0.141	—

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
Nº Ean13	3663952482804
Diâmetro interior	28 mm
Diâmetro exterior	42 mm
Espessura	30 mm
Peso	141 g
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE