


Rolamento de rolos NA49-28R-JTEKT - NA49-28R-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/rolos/na49-28r-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)			Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.	
F_w	d	D	B	B_1	r mm	C_r	C_{10}	Oil lub.	Grease lub.	Without inner ring	
32	28	45	17	—	0.3	25.0	33.8	14 000	—	—	
Mounting dimensions (mm)					(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.				
With inner ring					d_a max.	D_a max.	r_a max.	Without inner ring	With inner ring		
NA49/28R					30	43	0.3	0.075	0.099	IRM283217	

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
Nº Ean13	3663952482828
Diâmetro interior	28 mm
Diâmetro exterior	45 mm
Espessura	17 mm
Peso	99 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE