


Rolamento de rolos NA4907UU-JTEKT - NA4907UU-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/rolos/na4907uu-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 – 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)			Limiting speeds ¹⁾ (min ⁻¹)		Bearing No. Without inner ring
F_w	d	D	B	B_1	C_r	C_{10}	Oil lub.	With inner ring		
42	35	55	20	21	0.6	29.0	40.9	4 700	—	
Mounting dimensions (mm)					(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.			
With inner ring					Without inner ring	With inner ring				
NA4907UU					39	51	0.6	—	0.173	IRM354221

[Note] 1) Limiting speeds of bearing number NA49...UU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
Nº Ean13	3663952483108
Diâmetro interior	35 mm
Diâmetro exterior	55 mm
Espessura	20 mm
Peso	173 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE