


Rolamento de rolos NQI38-30-JTEKT - NQI38-30-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/rolos/nqi38-30-jtekt>

Machined ring needle roller bearings **Koyo**
F_w 29 ~ 37 mm

With inner ring



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No. Without inner ring
F _w	d	D	B	B ₁	C _r	C _{10r}	Oil lub.		
43	38	53	30	30	41.3	85.9	10 000	—	
Mounting dimensions (mm)					(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring					d _w min.	D _w max.	r _s max.	Without inner ring	With inner ring
NQI38/30					—	51	0.8	—	0.205

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
Nº Ean13	3663952483191
Diâmetro interior	38 mm
Diâmetro exterior	53 mm
Espessura	30 mm
Peso	205 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE