

Rolamento de rolos NQ60-25-JTEKT - NQ60-25-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/rolos/nq60-25-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 ~ 37 mm

Without inner ring



Boundary dimensions (mm)				Basic load ratings (kN)		Limiting speeds ¹⁾ (min ⁻¹)		Bearing No.
F_w	d	D	B	C_r	C_{10}	Oil lub.	Without inner ring	
60	—	72	25	45.4	97.3	7 900	NQ60/25	
Mounting dimensions (mm)				(Refer.) Mass (kg)		(Refer.) Applicable inner ring No.		
With inner ring				Without inner ring	With inner ring			
	d_a	D_a	r_a	0.164	—			
	max.	max.	max.					
	—	68	0.8					

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
Nº Ean13	3663952483603
Diâmetro interior	60 mm
Diâmetro exterior	72 mm
Espessura	25 mm
Peso	164 g
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE