

## Rolamento de rolos RNA4911R-JTEKT - RNA4911R-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/rolos/rna4911r-jtekt>

Machined ring needle roller bearings ————— **Koyo**  
F<sub>w</sub> 29 ~ 37 mm

Without inner ring



| Boundary dimensions (mm) |                |                |                | Basic load ratings (kN) |                 |                                    | Limiting speeds <sup>1)</sup> (min <sup>-1</sup> ) |                    | Bearing No. |
|--------------------------|----------------|----------------|----------------|-------------------------|-----------------|------------------------------------|--|--------------------|-------------|
| F <sub>w</sub>           | d              | D              | B              | C <sub>r</sub>          | C <sub>0r</sub> | Oil lub.                           |  | Without inner ring |             |
| 63                       | 55             | 80             | 25             | 58.4                    | 99.0            |                                    | 7 300  | <b>RNA4911R</b>    |             |
| Mounting dimensions (mm) |                |                |                | (Refer.) Mass (kg)      |                 | (Refer.) Applicable inner ring No. |  |                    |             |
| With inner ring          |                |                |                | Without inner ring      | With inner ring |                                    |  |                    |             |
|                          | d <sub>1</sub> | D <sub>1</sub> | r <sub>1</sub> | 0.260                   | 0.401           | IRM55G325                          |  |                    |             |
|                          | max.           | max.           | max.           |                         |                 |                                    |  |                    |             |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.  
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

## CARACTERÍSTICAS DO PRODUTO

|                   |               |
|-------------------|---------------|
| Marca             | JTEKT         |
| Nº Ean13          | 3663952483641 |
| Diâmetro interior | 63 mm         |
| Diâmetro exterior | 80 mm         |
| Espessura         | 25 mm         |
| Peso              | 260 g         |
| Embalagem         | 1             |

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE