


Rolamento de rolos NA5919-JTEKT - NA5919-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-rolos/rolos/na5919-jtekt>

Machined ring needle roller bearings Koyo

F_w 29 – 37 mm

With inner ring



| Boundary dimensions (mm) | | | | Basic load ratings (kN) | | Limiting speeds ¹⁾ (min ⁻¹) | | Bearing No. Without inner ring | |
|--------------------------|-----|-----|-----|-------------------------|-----------------|--|-------|-----------------------------------|------------|
| F_w | d | D | B | C_r | C_{10} | Oil lub. | | | |
| 110 | 95 | 130 | 46 | 141.0 | 331.0 | 4 200 | — | | |
| Mounting dimensions (mm) | | | | roller Mass (kg) | | roller Applicable inner ring No. | | | |
| With inner ring | | | | Without inner ring | With inner ring | | | | |
| NA5919 | | | | 101.5 | 123.5 | 1 | 0.940 | 1.78 | IRM9511046 |

[Note] 1) Limiting speeds of bearing number NA49. LU indicates the value of sealed and grease lubricated bearings.
[Remark] Limiting speed of grease lubrication should be kept to under 60 % of that for oil lubrication.

CARACTERÍSTICAS DO PRODUTO

| | |
|-------------------|---------------|
| Marca | JTEKT |
| Nº Ean13 | 3663952484181 |
| Diâmetro interior | 95 mm |
| Diâmetro exterior | 130 mm |
| Espessura | 46 mm |
| Peso | 1780 g |
| Embalagem | 1 |

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE