

Rolamento de agulhas 30205-XR-JTEKT - 30205-XR-JTEKT

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/agulhas/30205-xr-jtekt>

Boundary dimensions

Row Type	Grade	Basic load ratings (kN)	Fatigue load limit (kN)	Limiting speed (min ⁻¹)
Single row	Normal	30205, 30205A, 30205B, 30205C, 30205D, 30205E, 30205F, 30205G, 30205H, 30205J, 30205K, 30205L, 30205M, 30205N, 30205P, 30205Q, 30205R, 30205S, 30205T, 30205U, 30205V, 30205W, 30205X, 30205Y, 30205Z	38	7900
	Medium	30205C, 30205D, 30205E, 30205F, 30205G, 30205H, 30205J, 30205K, 30205L, 30205M, 30205N, 30205P, 30205Q, 30205R, 30205S, 30205T, 30205U, 30205V, 30205W, 30205X, 30205Y, 30205Z	38	7900
	High	30205C, 30205D, 30205E, 30205F, 30205G, 30205H, 30205J, 30205K, 30205L, 30205M, 30205N, 30205P, 30205Q, 30205R, 30205S, 30205T, 30205U, 30205V, 30205W, 30205X, 30205Y, 30205Z	38	7900
	Super	30205C, 30205D, 30205E, 30205F, 30205G, 30205H, 30205J, 30205K, 30205L, 30205M, 30205N, 30205P, 30205Q, 30205R, 30205S, 30205T, 30205U, 30205V, 30205W, 30205X, 30205Y, 30205Z	38	7900
Double row	Standard	46200, 46200A, 46200B, 46200C, 46200D, 46200E, 46200F, 46200G, 46200H, 46200J, 46200K, 46200L, 46200M, 46200N, 46200P, 46200Q, 46200R, 46200S, 46200T, 46200U, 46200V, 46200W, 46200X, 46200Y, 46200Z	38	7900
	ISO type	46200, 46200A, 46200B, 46200C, 46200D, 46200E, 46200F, 46200G, 46200H, 46200J, 46200K, 46200L, 46200M, 46200N, 46200P, 46200Q, 46200R, 46200S, 46200T, 46200U, 46200V, 46200W, 46200X, 46200Y, 46200Z	38	7900
Four row	Standard	61000, 61000A, 61000B, 61000C, 61000D, 61000E, 61000F, 61000G, 61000H, 61000J, 61000K, 61000L, 61000M, 61000N, 61000P, 61000Q, 61000R, 61000S, 61000T, 61000U, 61000V, 61000W, 61000X, 61000Y, 61000Z	38	7900
	ISO type	61000, 61000A, 61000B, 61000C, 61000D, 61000E, 61000F, 61000G, 61000H, 61000J, 61000K, 61000L, 61000M, 61000N, 61000P, 61000Q, 61000R, 61000S, 61000T, 61000U, 61000V, 61000W, 61000X, 61000Y, 61000Z	38	7900

Single row note: Primarily for use in the roll tracks of rolling mills.

Bearing No.	Boundary dimensions (mm)						Basic load ratings (kN)	Fatigue load limit (kN)	Limiting speed (min ⁻¹)	
	d	D	B	T	r ₁	r ₂	C ₁₀	C ₀₁₀	Speed limit	
30205XR	25	52	16.25	1.5	1	1	38	32.4	4.45	7900

CARACTERÍSTICAS DO PRODUTO

Marca	JTEKT
Nº Ean13	3616060628008
Diâmetro interior	25 mm
Diâmetro exterior	52 mm
Espessura	16.25 mm
Velocidade-limite	7900 rpm
Carga dinâmica	38 kN
Carga estática	32.4 kN
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE