


## Casquilho de agulhas BAM1016-IKO - BAM1016-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/casquilho-agulhas/bam1016-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
15.875 ( $\frac{5}{8}$ )	—	—	—	—	—	—	—	<b>BAM 1016</b>	18.4	—	—
Boundary dimensions mm(inch)		Standard mounting dimensions mm				Basic dynamic load rating	Basic static load rating	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring		
$F_w$	$D$	$C$	$b_2$ Shaft dia. h8 Max. Min.	Housing bore dia. J7 Max. Min.	$C$	$C_0$	Allowable rotational speed <sup>(1)</sup>	Assembled inner ring			
15.875 ( $\frac{5}{8}$ )	20.638 ( $\frac{3}{4}$ )	25.40(1.000)	1.3 Max. Min.	15.875 Max. Min.	20.650 Max. Min.	12 300	20 800	25 000	IRB 716		

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952172927
Diâmetro interior	15.88 mm
Diâmetro exterior	20.64 mm
Espessura	25.4 mm
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE