


## Casquilho de agulhas BAM108-IKO - BAM108-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/casquilho-agulhas/bam108-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number								
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g
15.875 (5/8)	—	—	—	—	—	—	<b>BAM 108</b>	9.9	—
Boundary dimensions mm(inch)		Standard mounting dimensions mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed(*)	Assembled inner ring
$F_w$	$D$	$C$	Shaft dia. h8 Max. Min.	Housing bore dia. J7 Max. Min.	$C$	$C_0$	$C_0$		
15.875 (5/8)	20.638 (3/4)	12.70 (500)	1.3 (15.875) 15.864	20.650 (20.629)	5 420	7 310	25 000	<b>IRB 68-1</b>	

Notes\*) Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952172958
Diâmetro interior	15.88 mm
Diâmetro interior	5/8" inch
Diâmetro exterior	20.64 mm
Diâmetro exterior	13/16" inch
Espessura	12.7 mm
Espessura	1/2" inch
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE