


Casquilho de agulhas BAM116-IKO - BAM116-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/casquilho-agulhas/bam116-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
17.462 ($\frac{3}{16}$)	—	—	—	—	—	—	—	BAM 116	B.4	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating	Basic static load rating	Allowable rotational speed ⁽¹⁾	Assembled inner ring	
F_w	D	C	Shaft dia. h_2	Housing bore dia. J_7	N	C_0	C_0	rpm	IRB 86		
17.462 ($\frac{3}{16}$)	22.225 ($\frac{7}{8}$)	9.521 ($\frac{3}{8}$)	1.3 Max.	17.462 Max.	17.451 Min.	22.237 Max.	22.216 Min.	4 530 N	5 980 N	25 000	IRB 86

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952172989
Diâmetro interior	17.46 mm
Diâmetro exterior	22.23 mm
Espessura	9.52 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE