


## Casquilho de agulhas BAM1210-IKO - BAM1210-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/casquilho-agulhas/bam1210-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



BAM BHAM

Shaft dia. mm (inch)	Identification number										
	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Standard	Mass (Ref.) g	Closed end	Mass (Ref.) g	Grease retained Mass (Ref.) g		
19.050 ( $\frac{3}{4}$ )	—	—	—	—	—	—	—	<b>BAM 1210</b>	18.6	—	—

Boundary dimensions			Standard mounting dimensions				Basic dynamic load rating		Basic static load rating		Allowable rotational speed <sup>(1)</sup>	Assembled inner ring
$F_w$	$D$	$C$	Shaft dia. $\phi$		Housing bore dia. $J7$		$C$	$C_0$	$N$	$N$	rpm	
			Max.	Min.	Max.	Min.	N	N	N			
19.050	25.400	15.881 (625)	1.3	19.050	19.037	25.412	25.391	9 500	13 200	20 000		<b>IRB #10-1</b>

Note<sup>(1)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952173009
Diâmetro interior	19.05 mm
Diâmetro exterior	25.4 mm
Espessura	15.88 mm
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE