


Casquilho de agulhas BAM126-IKO - BAM126-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/casquilho-agulhas/bam126-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Standard			Mass (Ref.) g			Grease retained g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end		
19.050 (3/4)	—	—	—	—	—	—	BAM 126	11.7	—	—	—

Boundary dimensions mm(inch)			Standard mounting dimensions mm			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾	Assembled (inner ring)
F _w	D	C	Shaft dia. h6 Max. Min.	Housing bore dia. J7 Max. Min.	Max. Min.	N	N	rpm	
19.050 3/4	25.400 1	9.52 .375	1.3	19.050 19.037	25.412 25.391	5 040	5 850	20 000	—

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952173047
Diâmetro interior	19.05 mm
Diâmetro exterior	25.4 mm
Espessura	9.52 mm
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE