


Casquilho de agulhas BAM1312-IKO - BAM1312-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/casquilho-agulhas/bam1312-iko>

IKO
SHELL TYPE NEEDLE ROLLER BEARINGS
Inch Series



Shaft dia. mm (inch)	Identification number			Identification number			Mass (Ref.) g	Grease retained g	Mass (Ref.) g
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end			
20.638 ($\frac{3}{4}$)	---	---	---	---	---	---	BAM 1312	23.5	---

Boundary dimensions			Standard mounting dimensions			Basic dynamic load rating C	Basic static load rating C ₀	Allowable rotational speed ⁽¹⁾ rpm	Assembled inner ring
F _w	D	C	Shaft dia. h6 Max. Min.	Housing bore dia. J7 Max. Min.	N				
20.638 $\frac{3}{4}$	26.988 $1 \frac{1}{8}$	19.051 $\frac{3}{4}$	20.638 Max.	20.625 Min.	27.000 Max.	26.979 Min.	12 400	19 000	19 000

Note⁽¹⁾ Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952173078
Diâmetro interior	20.64 mm
Diâmetro interior	13/16" inch
Diâmetro exterior	26.99 mm
Diâmetro exterior	1 1/16" inch
Espessura	19.05 mm
Espessura	3/4" inch
Embalagem	1

contato@123rolamento.pt

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE