


## Casquilho de agulhas BAM1614-IKO - BAM1614-IKO

<https://www.123rolamento.pt/rolamento-mancal/rolamento-agulhas/casquilho-agulhas/bam1614-iko>

**IKO**  
**SHELL TYPE NEEDLE ROLLER BEARINGS**  
Inch Series



Shaft dia. mm (inch)	Identification number			Identification number			Basic dynamic load rating C	Basic static load rating C <sub>0</sub>	Allowable rotational speed <sup>(*)</sup> rpm	Assembled inner ring	
	Standard	Mass (Ref.) g	Closed end	Standard	Mass (Ref.) g	Closed end					Mass (Ref.) g
25.400 (1)	—	—	—	—	—	—	<b>BAM 1614</b>	33.5	—	—	
Boundary dimensions mm(inch)		Standard mounting dimensions mm		Basic dynamic load rating		Basic static load rating		Allowable rotational speed <sup>(*)</sup>		Assembled inner ring	
$F_w$	$D$	$C$	$t$	Shaft dia. mm	Housing bore dia. mm	Max.	Min.	N	N	rpm	IRB 1214
25.400	31.750	22.22	2.8	25.400	25.387	31.764	31.739	16 900	30 400	15 000	IRB 1214

Note<sup>(\*)</sup> Allowable rotational speed applies to oil lubrication. For grease lubrication, a maximum of 60% of this value is allowable.  
Remark Shell Type Grease Retained Full Complement Needle Roller Bearings are provided with prepacked grease. Standard type and closed end type bearings are not provided with prepacked grease, so perform proper lubrication when using these types of bearings.

## CARACTERÍSTICAS DO PRODUTO

Marca	IKO
Nº Ean13	3663952173252
Diâmetro interior	25.4 mm
Diâmetro exterior	31.75 mm
Espessura	22.22 mm
Embalagem	1

[contato@123rolamento.pt](mailto:contato@123rolamento.pt)

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE